

RECEIVED
CENTRAL FAX CENTER

MAR 02 2009

IN THE CLAIMS:

Claim 1 (previously presented): An ultrasonic diagnostic apparatus for obtaining volume data made of voxel values for voxels forming a three-dimensional space by transmitting and receiving ultrasound to and from the three-dimensional space containing a target tissue and for applying a data process with respect to the volume data, the ultrasonic diagnostic apparatus comprising:

an isolated group extractor for extracting a plurality of isolated groups corresponding to the target tissues in the volume data;

a specific isolated group extractor for extracting an isolated group having a maximum volume from among the plurality of isolated groups as a specific isolated group in the volume data;

a basis axis setter for setting a basis axis in the specific isolated group based on a shape of the specific isolated group included in the plurality of isolated groups in the volume data;

a reference cross section setter for setting a plurality of reference cross sections each having a different rotational angle from each other, with the basis axis as an axis of rotation, in the volume data;

a basis cross section selector for selecting a basis cross section from among the plurality of reference cross sections based on a cross sectional area of the target tissue in each of the reference cross sections set in the volume data;

a cross sectional image former for forming a cross sectional image of the target tissue based on the volume data, the cross sectional image corresponding to one of cross sections set with the basis cross section as a reference and the basis cross section; and

a means for displaying said cross sectional image.

Claim 2 (previously presented): The ultrasonic diagnostic apparatus according to Claim 1, wherein

the basis axis setter sets the basis axis based on two characteristic points of the specific isolated group.

Claim 3 (previously presented): The ultrasonic diagnostic apparatus according to Claim 1, wherein

the basis axis setter sets the basis axis based on a center of mass of the specified isolated group and one characteristic point of the specified isolated group other than the center of mass.

Claim 4 (previously presented): The ultrasonic diagnostic apparatus according to Claim 1, wherein

the basis axis setter sets the basis axis based on the center of mass of the specified isolated group and an end, in the specified isolated group, which is furthest away from the center of mass.

Claim 5 (original): The ultrasonic diagnostic apparatus according to Claim 1, wherein the reference cross section setter sequentially rotates a specific plane containing the basis axis by a predetermined angle with the basis axis as an axis of rotation to set the planes formed in each rotational angle position as the plurality of reference cross sections.

Claim 6 (previously presented): The ultrasonic diagnostic apparatus according to Claim 1, wherein

the basis cross section selector calculates an area of a cross section of the target tissue in each reference cross section and selects, as the basis cross section, a reference cross section having a maximum cross sectional area.

Claim 7 (previously presented): The ultrasonic diagnostic apparatus according to Claim 1, wherein

the basis cross section selector calculates a cross sectional area of the target tissue in each reference cross section and selects, as the basis cross section, a reference cross section in which a minimum cross sectional area can be obtained.

Claim 8 (currently amended): An ultrasonic diagnostic apparatus for obtaining volume data made of voxel values for voxels forming a transmission space by transmitting and receiving ultrasound to or from a heart having four cavities including a left ventricle cavity and for applying a data process to the volume data, the ultrasonic diagnostic apparatus comprising:

a major axis setter for setting a left ventricle major axis based on the shape of the left ventricle cavity selected from the four cavities such that the left ventricle major axis passes a center of mass of the left ventricle cavity, in the volume data;

a reference cross section setter for setting a plurality of reference cross sections each having a different rotational angle from each other in the volume data, with the left ventricle major axis as an axis of rotation;

a basis cross section selector for selecting a basis cross section from among the plurality of reference cross sections based on a size of a cross section of the four cavities in each of the reference cross sections set in the volume data;

a cross sectional image former for forming a cross sectional image corresponding to ~~at least one~~ each of a four-cavity cross section, a two-cavity cross section, and a minor-axis cross section, all of which relate to the heart, based on the volume data and the basis cross section; and

a means for displaying said cross sectional image, wherein

the basis cross section selector calculates a cross sectional area of the four cavities in each of the reference cross sections and selects, as the basis cross section, a reference cross section in which a maximum cross sectional area can be obtained, and

the cross sectional image former sets the ~~reference basis~~ basis cross section as the four-cavity cross section, sets a cross section which is orthogonal to the basis cross section and includes the left ventricle major axis as the two-cavity cross section, and sets a cross section which is orthogonal to the left ventricle major axis and includes the center of mass of the left ventricle cavity as the minor axis cross section

~~the two-cavity cross section is a cross section which is orthogonal to the reference cross section and includes the left ventricle major axis, and~~

~~the minor axis cross section is a cross section which is orthogonal to the left cavity major axis and includes a center of mass of the left ventricle cavity.~~

Claim 9 (original): The ultrasonic diagnostic apparatus according to Claim 8, further comprising:

a binarization section for separating the voxels into cavity tissue voxels and real tissue voxels to create binarized volume data;

a cavity group extractor for extracting a plurality of cavity groups each made of a plurality of cavity tissue voxels based on the binarized volume data; and

a left ventricle cavity selector for selecting a left ventricle cavity group corresponding to the left ventricle cavity from among the plurality of cavity groups, wherein the major axis setter judges the shape of the left ventricle cavity based on the left ventricle cavity group.

Claim 10 (canceled).

Claim 11 (canceled).

Claim 12 (canceled).

Claim 13 (original): The ultrasonic diagnostic apparatus according to Claim 8, further comprising:

a three-dimensional image former for forming a three-dimensional image in which at least one cursor indicating at least one of the positions of the four-cavity cross section, the two-cavity cross section, and the minor-axis cross section is displayed on a stereographical image of the heart obtained based on the volume data.

Claim 14 (canceled).

Claim 15 (canceled).

Claim 16 (canceled).

Claim 17 (canceled).

Claim 18 (canceled).

Claim 19 (canceled).